

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

1                   1.       (Currently amended) A display apparatus comprising:  
2                   a front substrate on which a fluorescent material is provided;  
3                   a rear substrate disposed opposite to said front substrate and having a plurality of  
4 electron emission devices laid out thereon to form a matrix, each of said electron emission  
5 devices radiating electrons to said fluorescent material; and  
6                   a driver capable of applying two or more driving voltages sequentially, which are  
7 generated on the basis of an input video signal and have levels independent from each other,  
8 during a select period to at least one row of specific electron emission devices selected among  
9 said electron emission devices,  
10                  wherein said select period is divided into a plurality of sub-periods,  
11                  wherein each of said driving voltages is applied in each of said sub-periods and at  
12 least one of said driving voltages has a gray-scale level corresponding to a level of said input  
13 video signal.

1                   2.       (Original) A display apparatus according to claim 1 wherein:  
2                   said input video signal is a digital video signal; and  
3                   said two or more driving voltages are generated on the basis of a digital signal  
4 obtained as a result of converting the bit count of said digital video signal.

1                   3.       (Currently amended) A display apparatus comprising:  
2                   a rear substrate including:  
3                   a plurality of scanning electrodes extending in a screen horizontal  
4 direction;  
5                   a plurality of signal electrodes extended in a screen vertical direction; and

6 a plurality of electron emission devices placed at intersecting points of  
7 said scanning electrodes and said the signal electrodes, each of electron emission devices  
8 emitting electrons;

9 a front substrate disposed opposite to said rear substrate and provided with a  
10 fluorescent material emitting light due to electrons radiated thereto by said electron emission  
11 devices;

12 a scanning driver for applying to said scanning electrodes a select voltage for  
13 selecting at least one row of specific electron emission devices selected among said electron  
14 emission devices during a predetermined select period; and

15 a signal driver for applying to said signal electrodes a driving voltage having a  
16 level depending on an input video signal for driving said electron emission devices[[]].

17 wherein:

18 the duration of said select period is determined by the output period of  
19 said select voltage;

20 said select period is divided into a plurality of sub-periods; and

21 said driving voltage is applied in each of said sub-periods,

22 wherein a picture can be displayed with a gray-scale corresponding to the  
23 number of said divided sub-periods and to a gray-scale size determined by said driving  
24 voltage.

1 4. (Original) A display apparatus according to claim 3 wherein the level of  
2 said driving voltage applied to said signal electrodes is changed for each of said sub-periods.

1 5. (Currently amended) A display apparatus comprising:  
2 a plurality of scanning electrodes extended in a screen horizontal direction;  
3 a plurality of signal electrodes extended in a screen vertical direction;  
4 a screen on which a plurality of display devices are placed at intersecting points of  
5 said scanning electrodes and said signal electrodes to form a matrix;

6 a scanning driver for applying to said scanning electrodes a select voltage for  
7 selecting at least one row of specific display devices selected among said display devices during  
8 a predetermined select period; and

9 a driving signal generator capable of generating first and second driving signals,  
10 which have values independent from each other and each serve as a signal for driving said  
11 display devices, on the basis of an input video signal[[;]],

12 wherein:

13 the duration of said select period of said row of specific display devices is  
14 determined by said select voltage generated by said scanning driver; and

15 in said select period, driving voltages obtained on the basis of said first  
16 and second driving signals generated by said driving signal generator are applied  
17 consecutively to said signal electrodes,

18 wherein said select period is divided into a plurality of sub-periods,

19 wherein each of said driving voltages is applied in each of said sub-  
20 periods and at least one of said driving voltages has a gray-scale level corresponding to a  
21 level of said input video signal,

22 wherein a picture can be displayed with a gray-scale corresponding to the  
23 number of said divided sub-periods and to a gray-scale size determined by said driving  
24 voltage.

1 6. (Original) A display apparatus comprising:  
2 a plurality of scanning electrodes extended in a screen horizontal direction;  
3 a plurality of signal electrodes extended in a screen vertical direction;  
4 a screen on which a plurality of display devices are placed at intersecting points of  
5 said scanning electrodes and said signal electrodes to form a matrix;  
6 a scanning driver for applying to said scanning electrodes a select voltage for  
7 selecting at least one row of specific display devices selected among said display devices during  
8 a predetermined select period;

9 a driving signal generator capable of generating first and second driving signals,  
10 which have values independent from each other and each serve as a signal for driving said  
11 display devices, by conversion of the bit count of an input digital video signal;

12 a switch for outputting said first driving signal generated by said driving signal  
13 generator during a first period for the select period determined by an output period of the select  
14 voltage generated by said scanning driver and outputting said second driving signal generated by  
15 said driving signal generator during a second period for the select period determined by an  
16 output period of the select voltage generated by said scanning driver; and

17 a D/A converter for converting said first and second driving signals output by said  
18 switch into analog signals and for applying the analog signals to said signal electrodes as first  
19 and second driving voltages respectively.

1 7. (Original) A display apparatus according to claim 6 wherein:  
2 said display device includes an electron injection device for injecting electrons  
3 and a light emission layer for emitting light due to electrons (or holes) radiated thereto from said  
4 electron injection device; and

5 the number of electrons (or holes) radiated by said electron injection device is  
6 controlled by the select voltage applied to said scanning electrode connected to said display  
7 device and the driving voltage applied to said signal electrode connected to said display device.

1 8. (Original) A display apparatus according to claim 6 wherein the duration  
2 of said first sub-period is made different from the duration of said second sub-period.

1 9. (Original) A display apparatus according to claim 6 wherein:  
2 the duration of said first sub-period is made shorter than the duration of said  
3 second sub-period;

4 in an operation to produce a dark gray-scale display, gray-scale control is  
5 executed so as to set said second driving voltage applied in said second sub-period at a fixed  
6 level of no light emission and vary said first driving voltage applied in said first sub-period; and

7                   in an operation to produce a bright gray-scale display, gray-scale control is  
8   executed so as to set said first driving voltage applied in said first sub-period at a fixed level of a  
9   substantially maximum light emission and vary said second driving voltage applied in said  
10   second sub-period.

1                   10.   (Original) A display apparatus according to claim 6, further comprising  
2   an extraction circuit for extracting characteristics of said input video signal, wherein the  
3   durations of said first and second sub-periods or ranges of said driving voltages applied in said  
4   sub-periods are changed in accordance with characteristic extraction results output by said  
5   extraction circuit.

1                   11.   (Original) A display apparatus according to claim 6, further comprising a  
2   brightness or contrast setting unit, wherein the durations of said first and second sub-periods or  
3   ranges of said driving voltages applied in said sub-periods are changed in accordance with a  
4   brightness or contrast set value.

1                   12.   (Original) A display apparatus according to claim 6 wherein said driving  
2   signal generator is a gray-scale correction circuit having a function to correct a gray-scale  
3   characteristic's discontinuity caused by a combination of said first and second driving voltages  
4   applied in said first and second sub-periods respectively.

1                   13.   (Original) A display apparatus according to claim 6 wherein said driving  
2   signal generator generates said first and second driving signals by converting said digital video  
3   signal into a signal having a bit count greater than the bit count of said digital video signal.

1                   14.   (Original) A display apparatus according to claim 6 wherein the sum of  
2   the bit counts of said first and second driving signals generated by said driving signal generator  
3   is greater than the bit count of said digital video signal.

1                   15.     (Original) A display apparatus according to claim 6 wherein the bit counts  
2 of said first and second driving signals generated by said driving signal generator are each equal  
3 to the bit count of a digital signal that can be handled by said D/A converter.

1                   16.     (Original) A display apparatus according to claim 6 wherein said  
2 scanning driver outputs a select voltage for selecting two rows of said display devices at one time  
3 in a sequential scanning operation carried forward in said screen vertical direction.

1                   17.     (Original) A display apparatus according to claim 6 wherein said  
2 scanning driver outputs a select voltage for selecting two rows of said display devices at one time  
3 in a sequential scanning operation carried forward in said screen vertical direction in such a way  
4 that a select period of one of said two selected rows does not completely coincide with a select  
5 period of the other selected row.

1                   18.     (Original) A display apparatus according to claim 6 wherein said  
2 scanning driver outputs a select voltage for selecting at least one row of said display devices  
3 located on the upper half side of said screen and at least one row of said display devices located  
4 on the lower half side of said screen.

1                   19.     (Original) A signal driver employed in a display apparatus, said apparatus  
2 having a plurality of scanning electrodes extended in a screen horizontal direction; a plurality of  
3 signal electrodes extended in a screen vertical direction; a plurality of display devices placed at  
4 intersecting points of said scanning electrodes and said the signal electrodes; and a screen  
5 comprising said display devices laid out thereon to form a matrix; wherein said signal driver  
6 used for applying a driving voltage for driving said display devices to said signal electrode, said  
7 signal driver comprising:

8                   an n-bit gray-scale signal input terminal for inputting an n-bit gray-scale signal  
9 where  $n \geq 8$ ;

10                   A sub-period select signal input terminal for inputting a sub-period specification  
11 signal for specifying one of m sub-periods obtained as a result of dividing a select period of said  
12 scanning electrodes where  $m \geq 2$ ;  
13                   an output circuit for outputting k voltage levels where  $k \leq (\text{the } n\text{th power of } 2)/m$ ;  
14 and  
15                   a signal converter for selecting one of said k voltage (or current) levels on the  
16 basis of said n-bit gray-scale signal and said sub-period specification signal.

1                   20.   (Original) A display apparatus comprising:  
2                   a rear substrate including:  
3                   a plurality of scanning electrodes extended in a screen horizontal  
4 direction;  
5                   a plurality of signal electrodes extended in a screen vertical direction;  
6                   a plurality of electron emission devices placed at intersecting points of  
7 said scanning electrodes and said the signal electrodes, each of said electron emission devices  
8 emitting electrons;  
9                   a front substrate disposed opposite to said rear substrate and provided with a  
10 fluorescent material emitting light due to electrons radiated thereto by said electron emission  
11 devices; and  
12                   spacers placed between said rear substrate and said front substrate to create a  
13 space between said rear substrate and said front substrate;  
14                   wherein:  
15                   each specific one of said scanning electrodes is connected to two rows each  
16 comprising a group of specific electron emission devices;  
17                   said two rows each comprising a group of specific electron emission devices are  
18 connected respectively to two different ones of said signal electrodes; and  
19                   each of said spacers is located substantially at the center of said two rows each  
20 comprising a group of specific electron emission devices on said specific scanning electrode.

1                   21.     (Original) A display apparatus according to claim 20 wherein:  
2                   each two specific ones of said spacers are erected on different ones of said  
3 scanning electrodes to create a box-like configuration in conjunction with support members  
4 allowing said two specific spacers to support each other; and  
5                   the upper sides of said support members are placed at positions lower than the  
6 tops of said specific spacers and the lower sides of said support members are floated above the  
7 bottoms of the spacers at an altitude at least equal to the thickness of each of said scanning  
8 electrodes.

1                   22.     (Previously presented) A display apparatus according to claim 5 wherein:  
2                   said select period corresponds to at least two horizontal scanning periods.